

LED Guide | Product Reference

| Consultancy | Design | Supply | Installation | Maintenance | Funding

Flat Panel Lighting

Provides generous illumination, no glare and a direct replacement for suspended ceiling fluorescent fitting lighting units, available in all ceiling tile sizes.



Product	300 x 300	300 x 600	300 x 120	600 x 600	600 x 1200
Watts / Volts (AC)	18 / 180 to 240 ±10%	28 / 180 to 240 ±10%	39 / 180 to 240 ±10%	39 / 180 to 240 ±10%	66 / 180 to 240 ±10%
Cover	Milky	Milky	Milky	Milky	Milky
Colours	3000 and 6000 K	3000 and 6000 K	3000 and 6000 K	3000 and 6000 K	3000 and 6000 K
Lumens	1050	1800	2600	2500	4300
Beam Angle	105°	105°	105°	105°	105°
Rated Life	35,000 hrs	35,000 hrs	35,000 hrs	35,000 hrs	35,000 hrs
Ingress Protection	IP43	IP43	IP43	IP43	IP43
CRI	65/54	65/54	65/54	65/54	65/54

The Green Light Guarantee

We back our products with a three-year manufacturer's warranty. This means you not only get the green light on savings, but you also get the peace of mind that comes from knowing your investment is protected.

Onsite Renewables Ltd
Pantile Farm • Middle Lane
Bovingdon • Herts HP3 0LG

**Ready to switch on the savings?
Contact us today.**